



PRO PLUS+

100% SYNTHETIC, ESTER-FORTIFIED 4-STROKE ENGINE OIL

DESCRIPTION:

Full-synthetic, ester-fortified 4-stroke engine oil designed to ensure optimum protection, peak performance and positive clutch feel. Surface-active, oxidatively-stable formulation provides excellent film thickness while maintaining viscosity across all operating temperatures. Advanced, proprietary additive system keeps your engine running clean, trouble-free and extends the life of the machine. Exceeds the requirements of API SN PLUS / JASO MA2.

FEATURES & BENEFITS:

- Superior protection at any temperature
- Excellent clutch feel and clutch protection
- Shear stable, ester-fortified formula maintains oil viscosity and film thickness
- Proprietary additive system and synthetic base oils combine to minimize oxidation and wear
- Surface-active chemistry aggressively attaches to engine surfaces and keeps them clean
- Exceeds API SN PLUS and JASO MA2 specifications

APPLICATIONS:

For all air and water-cooled 4-stroke gasoline engines. For both racing and everyday use.

TECHNICAL DATA

| SPECIFICATION | TEST METHOD | 10W30 | 10W40 | 10W50 | 20W50 |
|-------------------------|-------------|-------|-------|-------|-------|
| APPEARANCE | VISUAL | Amber | Amber | Amber | Amber |
| VISCOSITY @ 40°C (cSt) | D445 | 65.6 | 89.3 | 127.9 | 133.4 |
| VISCOSITY @ 100°C (cSt) | D445 | 10.8 | 14.2 | 18.5 | 18.6 |
| VISCOSITY INDEX | D2270 | 156 | 165 | 163 | 157 |
| FLASH POINT (°C) | D92 | 205 | 207 | 222 | 218 |
| POUR POINT (°C) | D97 | -42 | -36 | -42 | -36 |
| DENSITY @ 15 °C (g/ml) | D4052 | 0.866 | 0.866 | 0.856 | 0.861 |

EXPERIENCE THE DIFFERENCE

Made In The USA